


## Process Pumps for Industry



# Lobee Pump & Machinery Co.

## Industrial Pumps and Accessories

Since 1899...Noted for Highest Quality Pumps and Equip-

Pulp/Paper, Plastics, Chemical, Pharmaceutical, Food & Beverage

Industrial Pumps for Stationary and Mobile Applications are available in Bronze, Stainless Steel, Nickel Alloy, and Cast Iron.



### HEAVY-DUTY GEAR PUMPS

#### Model LOS Bronze




1/2", 3/4" & 1" NPT Port Sizes. Flows to 18 GPM. Graphite Packing Standard

#### Model LOM



1/2", 3/4" & 1" NPT Port Sizes. Flows to 18 GPM. Mechanical Shaft Seal Standard

#### Model LOL



1/8", 1/4", 3/8", 1/2", 3/4", 1", 1-1/4" & 1-1/2" NPT Port Sizes. Flows to 90 GPM. Graphite Packing Standard

#### Model LOL-3



1/8", 1/4", 3/8", 1/2", 3/4", 1", 1-1/4" & 1-1/2" NPT Port Sizes. Flows to 90 GPM. Mechanical Shaft Seal Standard

#### Stainless Steel

#### Model LOE



1/4", 3/8", 1/2", 3/4" & 1" NPT Port Sizes. Flows to 18 GPM. PTFE Packing Standard

#### Model LOX



1/4", 3/8", 1/2", 3/4" & 1" NPT Port Sizes. Flows to 18 GPM. Mechanical Shaft Seal Standard

#### Cast Iron

#### Model LOI-3



3/8" & 3/4" NPT Port Sizes. Flows to 16 GPM. Mechanical Shaft Seal Standard

#### Model LOI



3/8" & 3/4" NPT Port Sizes. Flows to 16 GPM. Graphite Packing Standard

### VERTICAL SUMP PUMPS

Floor mounted and cover suspended models up to 130 GPM, 80' TDH. These are heavy-duty industrial continuous duty closed impeller pumps designed to last. Available in cast iron, stainless steel and bronze 'wetted' construction. Premium Efficient, TEFC, ODP, Washdown, and Explosion-Proof motors available in single or three phase voltage.



### DIRECT AND BASE MOUNTED PUMP UNITS

1/3 to 5 HP, Available in ODP, TEFC, Washdown or Explosion-Proof. Single or three phase, 1800 or 1200 RPM and inverter duty a standard option. Flows to 50 GPM, 150 PSI. Other options include mounted VFD, relief valve, special enclosure.



### LIQUID RING PUMPS

A versatile self-priming liquid ring pump design that excels at pumping combination liquid/vapor/gas. Vertical suction lift to 28 foot, flows to 80 GPM, total dynamic head to 230 feet.

Model CLR - 1", 1 1/2" and 2" NPT ports, 1800 RPM, Flows to 65 GPM, 160' TDH



Model CHLR - 1", 1 1/2" and 2" NPT ports, 3600 RPM, Flows to 80 GPM, 230' TDH



Model LR - 1", 1 1/2" and 2" NPT ports, 1800-3600 RPM, Flows to 80 GPM, 230' TDH. For direct drive applications



### FLOW RATERS

Our in-line flow indicators are available in 316 Stainless Steel, Brass and PVC. Port sizes are 1/2", 3/4" and 1" NPT, flows to 40 GPM



*100% Made in the USA by skilled craftsmen with over 100 years combined experience.*